

# WIND MESSE EMPEX- JAPAN

## FG-561

### Digital electronic Anemometer



Wind revolutions	Moment, maximum, minimum and average wind speed display
Measurement range	0 ~ 20 m / s (0-50 ° c)
Wind speed detection	Thermistor
Display unit	0.2 m / s (0-3 m / s), 0.5 m / s (4 to 20 m / s)
Precision	0 to 10 m / s (the displayed value $\pm$ 5%+0.2m/s)
Precision	10 ~ 20 m / s (the displayed value $\pm$ 10%)
Temperature (° c) measuring range	0 ~ + 50 ° c (1 sec per measurements)
Temperature detection	Thermistor
Precision	$\pm$ 0. 1 ° c (0 to + 40 ° c)
Precision	$\pm$ 0. 2 ° c (other than above)
Power supply	Two alkaline batteries 6 P type (9 V)
Battery life	About 8 hours with continuous use
Using temperature	0 to + 50 ° c
Material	ABS resin (paint finish)
Main unit dimensions	Vertical 160 (height) x 56 (horizontal) x 36 (depth) mm
Weight	Approx. 210 g (including batteries)
Accessories	Dedicated soft case, alkaline battery 6 P type (9 V) 2
Country of manufacture	Japan

www. EMPEX.co.jp

Zamin tavana tajhiz co. [www.ir-geo.com](http://www.ir-geo.com) 09121022203