

Items	Specification	Bk pol- 2R
Eyepiece	WF 10X-18mm	•
	WF 10X-18 mm (Reticule 0.1mm)	•
Non-stress Infinity Plan Objective	4x	•
	10x	•
	20x (S)	•
	40x (S)	•
	60x (S)	•
Seidentopf Binocular Head	Inclined 30°, Rotatable 360°, Interpupillary Distance: 50-75mm.	•
Trinocular Head	Inclined 30°, Rotatable 360°, Interpupillary Distance: 50-75mm. Light Distribution: 0:100	○
Nosepiece	Quintuple	•
Polarizing Unit	Rotatable 360°(Module Type, Can Be Locked)	•
Bertrand Lens	Inbuilt, Center Adjustable	•
$\lambda$ Slip	First Class Red	•
$1/4\lambda$ Slip		•
Quartz Wedge	( I -IV Class)	•
Revolving Round Stage	Rotatable 360°, Center Adjustable, Division 1°, Vernier division 6'	•
Polarizing Attached Mechanical Stage		○
Condenser	Abbe N.A. 1.25 Non-stress	•
Polarizing Unit with Scale	Rotatable 360°, Can Be Locked	•
Koehler Illumination	6V/20W Halogen Lamp	•
	6V/30W Halogen Lamp	○
2 A Fuse	Spare: 1 pc	•
Filter	Blue,	•
	Amber	○
	Green	○
	Neutral	○
C-mount	0.57x(Focus Adjustable), 1x	○
Adaptor for Digital Camera		○
Reflecting Polarizing Unit	Halogen Lamp House 12V/50W	•
	Power House	•
	Diaphragm Choosing Slide	•
	Polarizer Choosing Slide	•