all in one, bar graph LED + LCD

MOISTURE METER

Model: MS-7003 *ISO-9001, CE, IEC1010*







The Art of Measurement

Concrete/Wood, Red LED bar graph + LCD display

MOISTURE METER

Model: MS-7003

FEATURES

* Designed to check the moisture level of wood, concrete,
and other non-wood material.
* 6 % to 40 % moisture range on wood.
* 0 to 100% relative moisture value for Concrete and
other non-wood material.
* Red LED bar graph indicator and LCD digital display.
* All in one, meter build in the test pins.
* Optional separate probe, available for remote
measurement.
* Microprocessor circuit assures maximum possible
accuracy, provides special functions and features.
* Records Maximum & Minimum reading with recall.
* Data hold function to freeze the desired value on display.
* Heavy duty & compact housing case, designed for easy
carry out & operation.
* Built-in low battery indicator.

SPECIFICATIONS

Applications	Designed to check the moisture level of wood, concrete and other non-wood material.
Principal	Used the 2 pins electrode to measure the conductive ability of the species, then converter to the reading of % " Moisture of Content ".
Circuit	Custom one-chip of microprocessor LSI circuit.
Display	LCD size : 51 mm x 37 mm Digit size : 16 mm (0.62 ")

Range 0 to 100% relative moisture value for Concrete. and other non-wood material. Material 2: 6 % to 40 % moisture range on wood. Resolution 0.1 %. Accuracy \pm (5 % + 5 d) $=$ 23 \pm 5 °C $=$ Material 1: 13 % to 100% $=$ Material 2: 6 % to 40% Probe 2 pins moisture electrode. By push button on front panel.	
Material 2 : 6 % to 40 % moisture range on wood. Resolution 0.1 %. 4 (5 % + 5 d) @ 23± 5 °C @ Material 1 : 13 % to 100% @ Material 2 : 6 % to 40% Probe 2 pins moisture electrode.	
6 % to 40 % moisture range on wood. Resolution 0.1 %. 4 (5 % + 5 d) @ 23± 5 °C @ Material 1 : 13 % to 100% @ Material 2 : 6 % to 40% Probe 2 pins moisture electrode.	
Resolution 0.1 %. \(\text{1.5 \% + 5 d} \) \(\text{0.23\pm 5 \mathcal{C}} \) \(0.00000000000000000000000000000000000	
Accuracy $\pm (5 \% + 5 d)$ $@ 23 \pm 5 \%$ $@ Material 1 : 13 \% to 100\%$ $@ Material 2 : 6 \% to 40\%$ Probe 2 pins moisture electrode.	
@ 23± 5 ℃ @ Material 1 : 13 % to 100% @ Material 2 : 6 % to 40% Probe 2 pins moisture electrode.	
@ Material 1 : 13 % to 100% @ Material 2 : 6 % to 40% Probe 2 pins moisture electrode.	
@ Material 2 : 6 % to 40%Probe2 pins moisture electrode.	
Probe 2 pins moisture electrode.	
Data Hold By push button on front panel.	
Memory Recall Records Maximum & Minimum reading	
value.	
Sampling Time Approx. 0.8 second.	
Operating 0 to 50 $^{\circ}$ C (32 to 122 $^{\circ}$ F).	
Temp./Humidity Less than 80 %RH.	
Power Supply Alkaline 006P, MN1604 (PP3) DC 9V	
battery.	
Power Current Approx. DC 16 mA.	
Weight 251 g/0.55 LB.	
Dimension 216.5 x 68.5 x 29.7 mm	
(8.4 x 2.7 x 1.2 inch).	
Accessories Instruction manual 1 PC.	
Included Extra contact pins1 Set.	
Included Extra contact pins	
Included Extra contact pins1 Set.	

 $^{^{\}star}$ Appearance and specifications listed in this brochure are subject to change without notice.